



Aktivna zvučna kutija MYTHOS10 NOVA







Intelligent digital hi-band sound editor
(on-board optimization)




Dual band limiter for
independently stable performance




Digital time alignment and
generation for perfect sonic clarity



Extensive 3-channel DSP
with single-encoder interface



Digital hi-amp module
with 1,000 W power



Extra wide 90° beam angle
for advanced sound distribution

Ocjena:Neocjenjeno

Cijena
1185,00 KM

[Postavi pitanje vezano za ovaj proizvod](#)

Opis

10"/2-way self-powered loudspeaker /1.000 W

- High-class performance in ultra-lightweight design
- 1.000 W Class D bi-amped power module
- Extensive DSP featuring groundbreaking DTA2© technology
- IDSE© intelligent digital sound editor (on-board optimization)
- Single-encoder EASY CONTROL DSP interface
- DBL© dual-band limiters for independently stable performance
- Global master tuning presets and adjustable low-cut filter
- Graphic backlit screen (with locking function)
- Two combo inputs (XLR/6.3 jack with MIC/LINE switches)
- Two high-resolution microphone pre-amplifiers (in MIC mode)
- Rotatable high-frequency horn
- Rugged, texture-painted plywood enclosure
- Sophisticated high-sensitivity transducers
- Extra-wide 90° beam angle (for advanced sound distribution)

DTA2 digital time-alignment

The DTA2© digital time alignment algorithms provide for 100% matching, time-corrected and synchronized signals.

DTA2© combines the woofer with the high frequency driver to an acoustically detected single-point source across the entire listening area.

DTA2© inaugurates a next level of sonic clarity and total performance.

IDSE digital sound editor

The powerful IDSE© intelligent digital sound editor enables effective on-board optimization.

The editor includes a 3-band equalizer (± 12 dB), global master tuning presets and the adjustable low-cut filter at 80Hz, 100Hz, 120Hz and 150Hz (for operation with a self-powered subwoofer).

DBL dual band limiters

NOVA's DBL© dual-band limiters ensure for a stable performance at any level, independently operating from amplifier or DSP channel.

The limiters ensure stable mids and highs even at extreme bass impulses.

System Type: Self-powered 10" two-way, multifunctional vented cabinet

Frequency Range (-10 dB): 46 Hz - 22 KHz

Frequency Response (± 3 dB): 50 Hz - 20 KHz

Coverage Pattern: 90° x 60° nominal (HxV)

HF Horn: Moulded horn (rotatable)

Crossover Modes: Active / DSP

Crossover Frequency: 2.100 Hz

Power Rating (Continuous / Max.): 500 W / 1.000 W

Maximum SPL: 127 dB SPL peak

LF Driver: 1 x 10" NOVA 10/300 (2.5 in. voice coil)

LF Nominal Impedance: 8 Ohms

MF Driver: n/a

MF Nominal Impedance: n/a

HF Driver: 1 x NOVA T400, 1.75 in. voice coil comp. driver

HF Nominal Impedance: 8 ohms

Active Tunings: DSP

Enclosure: 15mm, birch plywood

Suspension / Mounting: 35 mm pole socket, 11 x M8 fixing points, 2 x M10 for U-Bracket monitor angle 35°, 7 x rubber feet

Transport: 1 integrated handle

Finish: Black spot painting

Grille: Powder coated, black, perforated steel with acoustic transparent foam front

Connectors: Input: 2 x XLR combo female, Mic / Line; Output: 1 x XLR mix output

Dimensions (W x H x D): 300 mm x 504 mm x 291 mm

Net Weight: 13 kg